



# SUPATAC EP-2 RED

## Extreme Pressure Grease

### Product Description

SUPATAC EP-2 RED is a premium quality grease blended with select high viscosity mineral oils in a lithium hydroxystearate soap thickener. Special lead free Extreme Pressure additives, rust and oxidation inhibitors with added tackiness agents, protects moving parts from shock loading, scuffing and wear. Excellent resistance to water washout ensures lubrication of equipment is maintained during wet and muddy conditions. SUPATAC EP-2 RED is recommended for heavy duty transport, construction equipment, off highway construction, mining, logging, forestry and material handling equipment.

### Technical Specifications

Tests	Typical Results
Appearance	Red & Tacky
NLGI	2
Penetration at 25°C	
Worked 60 Strokes	275
Worked 10,000 Strokes	292
Dropping Point. °C	192
Water Washout at 80°C, %	5
Wheel Bearing Leakage. g	3
Oxidation Resistance Pressure Drop. 100 hours, kpa	25
Timken. OK Load. Kg	28
4-Ball Weld. Kg/f	330
4-Ball Wear Scar. mm	0.48
Rust Prevention Characteristics	No rust
Mineral Oil Viscosity cSt at 40°C	300
Operating Temperature Range. °C	-20 °C to 130 °C

Product code: GRSREP2



ATLANTIC LUBRICANTS PTY LTD  
ABN: 67 088 335 059  
PO BOX 187  
INGLEBURN NSW 1890  
TELEPHONE: (02) 9829 7555  
FACSIMILE: (02) 9829 4555  
EMAIL: [general@atlanticlubricants.com.au](mailto:general@atlanticlubricants.com.au)  
WEB: [www.atlanticoil.com.au](http://www.atlanticoil.com.au)