



Atlantic CVT Ultra-Syn High Viscosity

Product Description

Atlantic CVT Ultra Syn High Viscosity is a full synthetic transmission fluid designed to service a multitude of Continuously Variable Transmissions. Atlantic CVT Ultra Syn High Viscosity has been manufactured using full synthetic base stocks and performance additives designed to provide optimal metal friction performance with excellent anti-shudder durability. Atlantic CVT Ultra Syn High Viscosity is suitable for almost all passenger vehicles fitted with Continuously Variable Transmissions providing superior low temperature performance and fluidity (-40°C Brookfield). The product meets best in class performance with a shear Stability of 40 hour KRL test. The fluid provides oxidation Performance equivalent to major OEM fluids.



Please Note: Atlantic CVT Ultra Syn Low Viscosity is not recommended for use in hybrid CVT units (Toyota and Ford).

Features & Benefits

- Exceptional thermal stability.
- Exceptional oxidation resistance and sludge control.

PRODUCT TECHNICAL CHARACTERISTICS

Property	Method	Units	
Viscosity, kinematic 40°C	ASTM D445	mm ² /s	35.0
Viscosity, Kinematic 100°C	ASTM D445	mm ² /s	7.0
Viscosity Index	ASTM D2270	None	168
Brookfield Viscosity At -40°C		mPa.s (cP)	12394

The above data is typical and does not constitute a specification.

All recommendations for the use of our products, whether given by us in writing, verbally, or to be implied from the results of tests carried out by us, are based on the current state of our knowledge. Notwithstanding any such recommendations the Buyer shall remain responsible for satisfying himself that the products as supplied by us are suitable for his intended process or purpose. Since we cannot control the application, use or processing of the products, we cannot accept responsibility therefore. The Buyer shall ensure that the intended use of the products will not infringe any third party's intellectual property rights. We warrant that our products are free from defects in accordance with and subject to our general conditions of supply.

Copyright © 2018 Atlantic Lubricants Pty Ltd. All rights reserved

Atlantic Lubricants Pty Ltd (ABN 67 088 335 059)

SYDNEY

40 Liverpool Street
Ingleburn NSW 2565
Ph: (02) 9829 7555
Fax: (02) 9829 4555

VICTORIA

6A Nicholas Drive
Dandenong South 3175
Ph: (03) 9768 3307
Fax: (03) 9768 2832

QUEENSLAND

Unit 2
7-9 Tradelink Road
Hillcrest QLD 4118
Ph: (07) 3556 1235

NEWCASTLE

31 Old Punt Road
Tomago NSW 2322
Ph: (02) 4964 8436

DARWIN

Unit 1A
894 Stuart Highway
Pinelands NT 0829
M: 0477 200 567

CANBERRA

P.O. Box 733
Gungahlin
ACT 2912
M: 0411 094 945

TASMANIA

42 - 44 Devonport Road
Quoiba 7310
Ph: (03) 6423 4900
Fax: (03) 6423 4800