

ATLANTIC NITRO GOLD PLUS 15W-40

Product Description:

Atlantic Nitro Gold Plus 15W-40 has been developed using the latest performance additives and Hydrocracked Group II base oils. Atlantic Nitro Gold Plus 15W-40 is designed to outperform conventional mineral oils in engine cleanliness and lubricity. Meeting the American Petroleum Institute's rating of SN for petrol engines, Atlantic Nitro Gold Plus is the perfect choice for modern multi-valve, turbo charged or supercharged engines.

Features and Benefits:

- Manufactured using water clear hydrocracked group II base stocks.
- Advanced additive technology provides increased film strength and hydrodynamic lubrication between metal surfaces.
- Reduced friction decreases fuel consumption and extends operating life of engine parts.
- API service classification of SN for gasoline engines ensures a wide range of vehicle compatibility
- Fully backward compatible with previous API specifications such as SM, SL, SH & SJ.



Typical Data:

Test Description	Method	Units	Results
Density @ 15°C	ASTM D 4052	kg/L	0.879
Viscosity, Kinematic @ 40°C	ASTM D 445	cSt	111
Viscosity, Kinematic @100°C	ASTM D 445	cSt	14.9
Viscosity Index	ASTM D 2270	-	139
Total Base Number (TBN)	ASTM D 2896	mgKOH/g	7.2
Cold Cranking Viscosity @ -20°C	ASTM D 5293	cP	6609
Flash Point	ASTM D 92	°C	210
Pour Point	ASTM D 97	°C	-27

Atlantic Lubricants Pty Ltd (ABN 67 088 335 059)

SYDNEY

40 Liverpool Street
Ingleburn NSW 2565
Ph: (02) 9829 7555
Fax: (02) 9829 4555

QUEENSLAND

P.O. Box 1250
Slacks Creek
QLD 4127
M: 0402 644 575

VICTORIA

6A Nicholas Drive
Dandenong South 3175
Ph: (03) 9768 3307
Fax: (03) 9768 2832

NEWCASTLE

31 Old Punt Road
Tomago NSW 2322
Ph: (02) 4964 8436

DARWIN

Unit 1A
894 Stuart Highway
Pinelands NT 0829
M: 0477 200 567

CANBERRA

P.O. Box 733
Gungahlin
ACT 2912
M: 0411 094 945

TASMANIA

42 - 44 Devonport Road
Quoiba 7310
Ph: (03) 6423 4900
Fax: (03) 6423 4800

PACK SIZE	PRODUCT CODE
5 Litre	PNG154P1
20 Litre	PNG154P2
60 Litre	PNG154P3
205 Litre	PNG154P4
1000 Litre	PNG154P5

Specifications/ Performance Levels:

- **SAE Viscosity:** 15W-40
- **API:** SN



All recommendations for the use of our products, whether given by us in writing, verbally, or to be implied from the results of tests carried out by us, are based on the current state of our knowledge. Notwithstanding any such recommendations the Buyer shall remain responsible for satisfying himself that the products as supplied by us are suitable for his intended process or purpose. Since we cannot control the application, use or processing of the products, we cannot accept responsibility, therefore. The Buyer shall ensure that the intended use of the products will not infringe any third party's intellectual property rights. We warrant that our products are free from defects in accordance with and subject to our general conditions of supply.

Copyright © 2022 Atlantic Lubricants Pty Ltd. All rights reserved.

30 September 2021

Atlantic Lubricants Pty Ltd (ABN 67 088 335 059)

SYDNEY

40 Liverpool Street
Ingleburn NSW 2565
Ph: (02) 9829 7555
Fax: (02) 9829 4555

QUEENSLAND

P.O. Box 1250
Slacks Creek
QLD 4127
M: 0402 644 575

VICTORIA

6A Nicholas Drive
Dandenong South 3175
Ph: (03) 9768 3307
Fax: (03) 9768 2832

NEWCASTLE

31 Old Punt Road
Tomago NSW 2322
Ph: (02) 4964 8436

DARWIN

Unit 1A
894 Stuart Highway
Pinelands NT 0829
M: 0477 200 567

CANBERRA

P.O. Box 733
Gungahlin
ACT 2912
M: 0411 094 945

TASMANIA

42 - 44 Devonport Road
Quoiba 7310
Ph: (03) 6423 4900
Fax: (03) 6423 4800