

ATLANTIC RACE BLEND 70

Product Description:

To satisfy the increased demands placed upon highly worked big block race engines incorporating flat tappet pushrod activated overhead valves, application specific race engine oils are an essential component in maintaining competitive advantage. Many race engines are fitted with oversize bearings subject to increased load requiring high viscosity base oils to protect metal surface integrity.

Pushrod activated overhead valves fitted with flat tappets require special consideration as the nature of these units place significant stress on cams.

Hydro dynamic lubrication is deficient in protecting cam wear, so the addition of special anti-wear agents is required to maintain acceptable camshaft service life. In consultation with world leading engine oil additive producers, engine builders and competition race enthusiasts, Atlantic Oils has developed Race Blend 70 to fully satisfy the demands placed upon highly worked big block race engines.

Atlantic Race Blend 70 is an SAE 40W-70 high viscosity race oil designed to offer unsurpassed protection of all race engine components. Advanced multigrade properties ensure fast oil flow during start-up. High viscosity base oils with the addition of special flow enhancers and viscosity modifiers ensure maximum oil film strength for bearings subject to high load even at cold start-up. The addition of zinc dialkyldithiophosphate (ZDDP) anti-wear agents offer protection of cams from the abrasive action of flat tappets. Unlike some zinc anti-wear agents which are thermally activated, Race Blend 70 offers full cam protection even at cold start-up. The addition of proprietary synthetic polymers ensures that upper engine parts retain a protective oil film even after intervals of non-use offering substantial wear reduction during start-up.



Features and Benefits:

- Multigrade properties with the addition of flow enhancers ensures fast oil flow during cold starts.
- Group II hydrocracked high viscosity base oils ensures maximum protection of all moving parts especially oversized bearings under high load conditions.
- The addition of zinc dialkyldithiophosphate protects cams against the abrasive action of flat tappets.
- The addition of specially selected synthetic polymers ensures all upper engine parts retain a protective oil film, even after periods of non-use.
- High viscosity properties reduce the effect of lubricant thinning where methanol fuels are used.

Atlantic Lubricants Pty Ltd (ABN 67 088 335 059)

SYDNEY

40 Liverpool Street
Ingleburn NSW 2565
Ph: (02) 9829 7555
Fax: (02) 9829 4555

QUEENSLAND

P.O. Box 1250
Slacks Creek
QLD 4127
M: 0402 644 575

VICTORIA

6A Nicholas Drive
Dandenong South 3175
Ph: (03) 9768 3307
Fax: (03) 9768 2832

NEWCASTLE

31 Old Punt Road
Tomago NSW 2322
Ph: (02) 4964 8436

DARWIN

Unit 1A
894 Stuart Highway
Pinelands NT 0829
M: 0477 200 567

CANBERRA

P.O. Box 733
Gungahlin
ACT 2912
M: 0411 094 945

TASMANIA

42 - 44 Devonport Road
Quoiba 7310
Ph: (03) 6423 4900
Fax: (03) 6423 4800

Typical Data:

Test Description	Method	Units	Results
Density @ 15°C	ASTM D 4052	kg/L	0.889
Viscosity, Kinematic @ 40°C	ASTM D 445	cSt	285
Viscosity, Kinematic @100°C	ASTM D 445	cSt	27.5
Viscosity Index	ASTM D 2270	-	128
Zinc	-	% wt.	0.150

Specifications/ Performance Levels:

- **SAE Viscosity: 40W-70**

PACK SIZE	PRODUCT CODE
5 Litre	RAC40701
20 Litre	RAC40702
60 Litre	RAC40703
205 Litre	RAC40704



All recommendations for the use of our products, whether given by us in writing, verbally, or to be implied from the results of tests carried out by us, are based on the current state of our knowledge. Notwithstanding any such recommendations the Buyer shall remain responsible for satisfying himself that the products as supplied by us are suitable for his intended process or purpose. Since we cannot control the application, use or processing of the products, we cannot accept responsibility, therefore. The Buyer shall ensure that the intended use of the products will not infringe any third party's intellectual property rights. We warrant that our products are free from defects in accordance with and subject to our general conditions of supply.

Copyright © 2022 Atlantic Lubricants Pty Ltd. All rights reserved.

27 October 2021

Atlantic Lubricants Pty Ltd (ABN 67 088 335 059)

SYDNEY

40 Liverpool Street
Ingleburn NSW 2565
Ph: (02) 9829 7555
Fax: (02) 9829 4555

QUEENSLAND

P.O. Box 1250
Slacks Creek
QLD 4127
M: 0402 644 575

VICTORIA

6A Nicholas Drive
Dandenong South 3175
Ph: (03) 9768 3307
Fax: (03) 9768 2832

NEWCASTLE

31 Old Punt Road
Tomago NSW 2322
Ph: (02) 4964 8436

DARWIN

Unit 1A
894 Stuart Highway
Pinelands NT 0829
M: 0477 200 567

CANBERRA

P.O. Box 733
Gungahlin
ACT 2912
M: 0411 094 945

TASMANIA

42 - 44 Devonport Road
Quoiba 7310
Ph: (03) 6423 4900
Fax: (03) 6423 4800