

ATLANTIC SUPERTRONIC 15W-40 CI-4

Product Description:

Atlantic Supertronic 15W-40 CI-4 is a modern diesel engine oil designed for heavy duty applications. It has been blended from hydrocracked base stocks and a premium additive package. Supertronic 15W-40 CI-4 is suitable for turbocharged and naturally aspirated engines providing superior soot dispersing additives to ensure consistent lubricant viscosity throughout the service interval. It is suitable for servicing most light/ heavy duty on & off road vehicles, earthmoving machinery, agricultural tractors as well as industrial equipment. Supertronic 15W-40 CI-4 is however not recommended for diesel engines fitted with EGR and exhaust emission reduction systems such as DPF, CPF, DOC and or SCR. Always refer to the Atlantic Lube Guide for correct product application.

Features and Benefits:

- Premium engine protection
- Superior Sludge and viscosity increase control
- Provides outstanding performance in reducing oxidation
- Improved piston deposit protection
- Mid ash formulation minimises combustion deposits
- Suitable for use where API: CH-4, CG-4 or CF-4 is specified



Typical Data:

Test Description	Method	Units	Results
Density @ 15°C	ASTM D 4052	kg/L	0.878
Viscosity, Kinematic @ 40°C	ASTM D 445	cSt	113
Viscosity, Kinematic @100°C	ASTM D 445	cSt	14.9
Viscosity Index	ASTM D 2270	-	136
Cold Cranking Viscosity	ASTM D 5293	cP @ -20°C	-
Total Base Number (TBN)	ASTM D 2896	mgKOH/g	10.3
Flash Point	ASTM D 93	°C	212
Pour Point	ASTM D 97	°C	-39
Sulfated Ash	ASTM D 874	% wt.	1.39

Atlantic Lubricants Pty Ltd (ABN 67 088 335 059)

SYDNEY

40 Liverpool Street
Ingleburn NSW 2565
Ph: (02) 9829 7555
Fax: (02) 9829 4555

QUEENSLAND

P.O. Box 1250
Slacks Creek
QLD 4127
M: 0402 644 575

VICTORIA

6A Nicholas Drive
Dandenong South 3175
Ph: (03) 9768 3307
Fax: (03) 9768 2832

NEWCASTLE

31 Old Punt Road
Tomago NSW 2322
Ph: (02) 4964 8436

DARWIN

Unit 1A
894 Stuart Highway
Pinelands NT 0829
M: 0477 200 567

CANBERRA

P.O. Box 733
Gungahlin
ACT 2912
M: 0411 094 945

TASMANIA

42 - 44 Devonport Road
Quoiba 7310
Ph: (03) 6423 4900
Fax: (03) 6423 4800

PACK SIZE	PRODUCT CODE
5 Litre	DST15401
20 Litre	DST15402
60 Litre	DST15403
205 Litre	DST15404
1000 Litre	DST15405

Specifications/ Performance Levels:

- **API:** CI-4/ SL
- **ACEA:** E7
- **Allison:** C4
- **Caterpillar:** ECF 2, ECF-1A
- **Cummins:** CES 20078
- **Daimler:** 228.3
- **Detroit Diesel:** DDC 93K215
- **Deutz:** DQC III-10
- **Global:** DHD-1
- **JASO:** DH-1
- **Mack:** EO-M Plus, EO-N
- **MAN:** M 3275
- **MTU:** Category 2
- **Renault:** RLD-2
- **Volvo:** VDS-3



All recommendations for the use of our products, whether given by us in writing, verbally, or to be implied from the results of tests carried out by us, are based on the current state of our knowledge. Notwithstanding any such recommendations the Buyer shall remain responsible for satisfying himself that the products as supplied by us are suitable for his intended process or purpose. Since we cannot control the application, use or processing of the products, we cannot accept responsibility, therefore. The Buyer shall ensure that the intended use of the products will not infringe any third party's intellectual property rights. We warrant that our products are free from defects in accordance with and subject to our general conditions of supply.

Copyright © 2020 Atlantic Lubricants Pty Ltd. All rights reserved.

15 May 2020

Atlantic Lubricants Pty Ltd (ABN 67 088 335 059)

SYDNEY

40 Liverpool Street
Ingleburn NSW 2565
Ph: (02) 9829 7555
Fax: (02) 9829 4555

QUEENSLAND

P.O. Box 1250
Slacks Creek
QLD 4127
M: 0402 644 575

VICTORIA

6A Nicholas Drive
Dandenong South 3175
Ph: (03) 9768 3307
Fax: (03) 9768 2832

NEWCASTLE

31 Old Punt Road
Tomago NSW 2322
Ph: (02) 4964 8436

DARWIN

Unit 1A
894 Stuart Highway
Pinelands NT 0829
M: 0477 200 567

CANBERRA

P.O. Box 733
Gungahlin
ACT 2912
M: 0411 094 945

TASMANIA

42 - 44 Devonport Road
Quoiba 7310
Ph: (03) 6423 4900
Fax: (03) 6423 4800